



SF-540A

1. Functional features

- 1.1 Mirror chrome plating roller, oil heating
- 1.2 Touch screen interaction display system
- 1.3 Auto feeding with air suction
- 1.4 Pneumatic auto separation
- 1.5 Heavy duty construction
- 1.6 20m/min laminating speed
- 1.7 Curling-preventing device, preventing laminated paper from curling;
- 1.8 Digital foiling
- 1.9 Large feeding volume, 2500 sheets, 200gsm paper
- 1.10 Automatic stop function for paper shortage.

2. Technical parameter

Technical parameters	Model	SF-540A
	Max. size of roll film	0.53m ×3000 m
	Film thickness range	17Mic~38Mic
	Applicable dimension of reel for roll	φ75mm

Sunfung Technology Corporation Ltd

film		
Max. O.D. dimension of roll film	Φ300mm	
Applicable thickness of paper core	Laser printing paper	128~450g/m ²
	Printing paper	157~350g/m ²
Max. applicable size of printed matter	540×760mm	
Min. applicable size of printed matter	297×420 mm	
Speed regulation range	1~20m/min	
Temperature regulation range	80~140℃	
Preheating time	20℃At room temperature 15min (100℃)	
Operation and display system	touch screen	
Pressurization mode	hydraulic pressure	
Heating mode	Oil heating	
Laminating roll diameter	Upper roll	High gloss chromium plating 160mm
	Lower roll	silicon rubber 100mm
Paper overlap accuracy	±2mm	
Rated input power	6500W	
Rated input voltage	220~240VAC, 50/60Hz	
Allowable voltage fluctuation	+/-10%	
Allowable frequency fluctuation	+/-10%	
Net weight of complete machine	435Kg	
Gross weight of machine	510Kg	
Machine transport dimensions (L × W × H)	1500×1150×1350mm	

Sunfung Technology Corporation Ltd

No 259 Wensan Road, Xihu District, Hangzhou, 310000 CHINA

Tel: 0086-571 85175095

Web: <https://sunfung-tech.com>

Email: info@sunfung-tech.com